




7k-0266

AL0918 Piston Pump Data

11.6 BHP Continuous Duty (13.8 BHP Intermittent Duty)



Specifications	
Pump Model	AL0918
Configuration	Horizontal Triplex Piston
Number of Pistons	3
Stroke Length	2.25 Inches (57.2 mm)
Frame Load Rating	2800 lbs. (1,270 kg)
Pump Weight	200 lbs. (90.7 kg)
Direction of Rotation	Top of Shaft away from head
Internal Gear Rotation	3.6:1
Intermittent Duty Speed Rating	890 RPM (Jackshaft)
Continuous Duty Speed Rating	750 RPM (Jackshaft)
Ball Valve Max Speed Rating	625 RPM
Minimum Speed	360 RPM
Mechanical Efficiency	85%
Lubrication System	Splash, Gravity Return
Lube Oil Capacity	2.25 Quarts
Lube Oil Type	SAE 30
Maximum Fluid Temperature	140 °F (250 °F Capability)
Minimum Fluid Temperature	0 °F (-20 °F Capability)
Standard Suction Size	1.50 Inch NPT (38.1 mm)
Standard Discharge Size	1.00 Inch NPT (25.4 mm)
Fluid End Material	Cast Iron
Valve Type	Disc Valve / Ball Valve
Hydraulic Motor Mount	SAE C - 4 Bolt with 1.25"-14T

AL0918B Performance Rating

Diameter		Displacement/REV		Maximum Pressure		Pump Capacity @ Input Speed (RPM)									
Inch	mm	Gallon	Liter	PSI	kg/cm ²	350 RPM		625 RPM		700 RPM		750 RPM		890 RPM	
						gpm	lpm	gpm	lpm	gpm	lpm	gpm	lpm	gpm	lpm
2.25	57.2	0.0323	0.122	700	49.2	11.3	43	20.2	76	22.6	86	24.2	92	28.7	109

Specifications subject to change without notice.

Horsepower is based on 85 or 90% efficiency. Actual application horsepower requirements can be calculated using this equation: $BHP = (GPM * PSI) / (1714 * 0.85 \text{ or } 0.90)$ Pump capacities listed are based on 100% volumetric efficiency.

This document contains American Mfg Company proprietary and confidential information. It is loaned for limited purposes only and remains the property of American Mfg Company. It may not be reproduced in whole or part or disclosed to third parties without the prior written consent of American Mfg Company. The document is to be returned to American Mfg Company upon request and in all events upon completion of the use for which it was used.



AL0918B Component Item Numbers

Item #	Component Description	Part #	Qty
1	Power Frame	PPFMC 5260537	1
2	Crankshaft	PPFMC 1279071	1
3	Pinion Shaft	PPFMC 1265098	1
4	Connecting Rod Assembly	PPFMC 18710	3
5	Rod Bearing	PPFMC P506697	3
6	Wrist Pin	PPFMC A5006	3
7	Crosshead Assembly	PPFMC 1250876	3
8	Seal Holder	PPFMC 1283601	3
9	Oil Seal, Piston Rod	PPFMC 1283603	6
10	Seal Retainer Nut	PPFMC 1283600	3
11	Gasket, Seal Retainer	PPFMC 1283602	3
12	Bearing Housing, Blind	PPFMC 1279064	2
13	Shim, Bearing Housing	PPFMC 1257594	5
14	Gasket, Bearing Housing	PPFMC A5025	2
15	Back Cover	PPFMC 1279063	1
16	Gasket, Back Cover	PPFMC 1279065	1
17	Pinion Housing, Drive	PPFMC A5005	1
18	Pinion Housing, Blind	PPFMC 1225769	1
19	Petcock	PPFMC 1187039	1
20	Gasket, Pinion	PPFMC A5026	2
21	Nameplate	PPFMC 5277981	1
22	Lube Fitting	PPFMC 1100759	3
23	Bearing Cone, Crank	PPFMC 1101242	2
24	Bearing Cup, Crank	PPFMC 1177287	2
25	Bearing, Pinion	PPFMC 1104444	2
26	Key	PPFMC 1187577	1
27	Cap screw, Pinion Bearing	PPFMC 1100068	12
28	Screw	PPFMC 1187413	2
29	Cap Screw, Back Cover	PPFMC 1106910	14
30	Set Screw	PPFMC 1103470	3

Item #	Component Description	Part #	Qty
31	Plate, Inspection	PPFMC 1214260	1
32	Pipe Plug, Power End	PPFMC 1187048	2
33	Filler Cap or Vent	PPFMC A5054	1
34	Screw	PPFMC 1106980	2
38	Fluid Chamber	PPFMC 1255266	1
39	Valve Seat	PPFMC 1225327	6
40	Piston Cup	PPFMC A3434N	3
41	Piston Holder	PPFMC 8495	3
42	Hex Nut	PPFMC 8309	3
43	Nut Retainer	PPFMC A5016	3
44	Piston Retainer	PPFMC 1207289	3
45	O-Ring, Rod Seal	PPFMC 1101176	3
46	Gasket, Fluid Chamber	PPFMC 1280024	6
47	Plug, Pipe	PPFMC P501267	6
48	Plug, Suction	PPFMC 1105105	2
49	Valve Cover	PPFMC A5003	3
50	Gasket, Valve Cover	PPFMC 1280026	3
51	Clamp, Valve Cover	PPFMC 1271716	3
52	Stud, Valve Cover	PPFMC A5012	6
53	Hex Nut, Valve Cover	PPFMC 1121511	14
54	Cylinder Cover	PPFMC A5002	3
55	Gasket, Cylinder Cover	PPFMC 1280025	3
56	Cylinder	PPFMC 1272060	3
57	Clamp, Cylinder	PPFMC 1271415	3
58	Stud, Cylinder Cover	PPFMC A5011	6
59	Stud	PPFMC A5009	2
60	Seal Holder	PPFMC 1281655	3
61	Hex, Nut, Cylinder	PPFMC 1121511	8
62	Ball	PPFMC 1187738	6

